

Fast and energy saving

TDR 8 Programmable eco

The Turbo Deli Rotisserie is the fastest original rotisserie in the industry. The TDR's cavity is fed with air, cooking a rotisserie chicken as it is meant to be: crispy and delicious while maintaining an attractive appearance for hours.

The TDR pushes the air throughout the cavity, resulting in an improved heat transfer on the products and consequently in a reduced electricity consumption during the preparation process.

Thanks to eco-cooking the TDR saves an additional 5% on energy. Add to this the improved heat transfer on the products and a fast preparation process and you have yourself the most energy-efficient rotisserie with a high output.

The Cook Correction Technology corrects alterations in the cooking cycle that are due to half-loads, overloads, or products with a difference in temperature. It measures abnormalities in the temperature curve and corrects the cycle automatically, ensuring food-safety and energy-efficient cooking.



Features TDR 8 Programmable

Top features

- Controls with programmable settings
- 99 programs with up to 3 cook stages per program
- Efficient heat transfer reduces energy consumption
- Cook correction to control food safety
- Eco-cooking, saves on energy consumption

Standard characteristics

- 8 Meat fork or V-spit positions, 7 basket or rack positions
- Rotor for up to 40 chickens (1.2 kg) per batch
- USB connection for easy transfer of data and programs
- Boost functionality to add extra time
- Outstanding food quality: high-speed convection for even cooking
- Outstanding food quality: radiant heat for uniform browning
- Striking cooking theatre due to large glass surface and brilliant lighting
- Safety stop when opening the door
- No water and drain connections needed

Accessories

- Meat forks (included)
- Multi-purpose baskets
- V-spits and chicken racks
- Matching stand on castors

Optional


- Double stacked unit



Programmable controls



Eco-cooking



Ventless hood (optional)



Large product view

TDR 8 Programmable

- 1 Power cable 2.2 m
- 2 Exhaust opening
- 3 Space to the wall
- 4 Location for socket

Dimensions TDR 8

| | |
|-----------------|---------|
| Width | 995 mm |
| Depth | 836 mm |
| Height | 1065 mm |
| Height on stand | 1796 mm |

Technical data TDR 8

| | |
|--------------|---------------|
| Net weight | 185 kg |
| Gross weight | 216 kg |
| Voltage | 3N~ 400/230 V |
| Frequency | 50/60 Hz |
| Power | 10.5 kW |

Dimensions TDR 8+8

| | |
|--------|---------|
| Width | 995 mm |
| Depth | 836 mm |
| Height | 2095 mm |

Technical data TDR 8+8

| | |
|--------------|---------------|
| Net weight | 375 kg |
| Gross weight | 435 kg |
| Voltage | 3N~ 400/230 V |
| Frequency | 50/60 Hz |
| Power | 21 kW |

Specifications and technical data are subject to amendment without prior notice.

These are basic drawings. For more detailed technical information, please refer to the installation manual at www.frijado.com.

